



## Spectroscopy in high- temperature industrial processes on Earth

**Fateev, Alexander**

*Publication date:*  
2015

*Document Version*  
Peer reviewed version

[Link back to DTU Orbit](#)

*Citation (APA):*  
Fateev, A. (Author). (2015). Spectroscopy in high- temperature industrial processes on Earth. Sound/Visual production (digital)

---

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.


# Spectroscopy of Exoplanets | Spectroscopy in high- temperature industrial processes on Earth

July 24<sup>th</sup> – 26<sup>th</sup> 2015

Senior Scientists **Alexander Fateev**




DTU Chemical Engineering  
Department of Chemical and Biochemical Engineering



# Spectroscopy in industrial processes | Outline

- **Background**
- **Large scale measurements**
- **Example/Case 1: NH<sub>3</sub>**
- **Example/Case 2: SO<sub>2</sub>/SO<sub>3</sub>**
- **Example/Case 3/UV: C<sub>6</sub>H<sub>6</sub>O and C<sub>10</sub>H<sub>8</sub>**
- **Conclusions**




## Needs | Large Scale Measurements

- Boilers,
- Flames (oil, gas, bio-masses),
- Engines (ships, jets),
- Field campaigns (explosions)



VIS image grade flame (waste)



IR image wood dust flame (video fuel mixing)




# Complexity | Large Scale Measurements

## Complexity:

- get results first
- trustful system
- 1500C is not uncommon

## Expensive:

- access possibilities
- man power
- time



# Data analysis | Large Scale Measurements

## Data analysis:



- on-line
- at home

## Source of reference data:


- measurements in a cell with pre-mixed gases
- databases (IR/UV)

NO measurements in exhaust duct of a large ship engine

DTU Chemical Engineering  
Department of Chemical and Biochemical Engineering



## Example 1 | NH<sub>3</sub>: experiment (500C, 0.09cm<sup>-1</sup>) vs calculations (BYTe)



### More details:

Emma J. Barton et al


“High-resolution absorption measurements of NH<sub>3</sub> at high temperatures: 500 - 2100 cm<sup>-1</sup>”  
(submitted to JQSRT)

**DTU Chemical Engineering**  
Department of Chemical and Biochemical Engineering

Can we use BYTe at 500C for practical apps?



- in general a good agreement
- some difficulties with strong line intensities
- some frequency shifts in line positions

More work to do at even higher T (>500C)



## Application case 1 | In Situ measurements on **Pyroener (6MW) gasifier**

**NH<sub>3</sub>: Q: Why to do measurements? A: NH<sub>3</sub> contributes to NO<sub>x</sub> formation**



### Gas extraction (150C):

20-06-2014 (17:00-19:30) : **NH<sub>3</sub>=(0.4 ± 0.02)%**, H<sub>2</sub>O=(35 ± 0.6)%, CO<sub>2</sub>=(14 ± 0.45)%, CO=(10 ± 0.21)%

24-06-2014 (15:00-17:00): **NH<sub>3</sub>=(0.42 ± 0.02)%**, H<sub>2</sub>O=(36 ± 0.6)%, CO<sub>2</sub>=(13.5 ± 0.45)%, CO=(10.3 ± 0.21)%

### In situ (547C):



24-06-2014 (20:00-21:00): **NH<sub>3</sub>=(0.55 ± 0.05)%**, H<sub>2</sub>O=(36 ± 1)%



# Application case 2 | SO<sub>2</sub>/SO<sub>3</sub>/NH<sub>3</sub> in a hot flue gas


**SO<sub>2</sub>/SO<sub>3</sub>/NH<sub>3</sub>: Q: Why to do measurements?**

**A: NO<sub>x</sub> reduction at SCR/NSCR units, NH<sub>3</sub> slip/costs, corrosion/fouling**



## Example 2 | SO<sub>3</sub>: measurements at 25C and 400C

SO<sub>3</sub> at 25C: 0.5cm<sup>-1</sup> vs PNNL (0.12cm<sup>-1</sup>)




- Simple to generate, but difficult to measure/quantify
- No databases (SO<sub>2</sub>/SO<sub>3</sub>) are available at T>100C


### Good news:

- Excellent agreement with PNNL data at 25C
- No need to use high-resolution at high T

T=400C SO<sub>3</sub>: effect of resolution 0.5cm<sup>-1</sup> vs 0.09 cm<sup>-1</sup>




## Example 2 | SO<sub>2</sub>/SO<sub>3</sub> cross sections (0.5cm<sup>-1</sup>)




PhD (Dan Underwood) with UCL:

- SO<sub>2</sub> and SO<sub>3</sub> line lists
- ready by the end 2015
- **2<sup>nd</sup> Power plant measurement campaign, fall 2015**




- Not too many reference data available even at low T (about 23C)
- An excellent agreement with published data at low T
- Significant changes in the fine structure of the cross-section spectra with T

Naphthalene abs cross-sections: from 23C to 500C




Phenol abs cross-sections: from 23C to 500C



# Application case 3/UV | In Situ measurements on LT-CFB (100kW) gasifier

**Phenol/Naphthalene: Q: Why to do measurements?**




**A: Phenol/Naphthalene – major trace gases from PAH's in low temperature gasification**



Few new challenges:

- Very strong UV light attenuation
- Very broad continuum-like abs structures
- Very small L for in situ measurements



DOAS approach: SO<sub>2</sub> UV absorption as an example





# Application case 3/UV | In Situ measurements on LT-CFB (100kW) gasifier

## Comparison of the measurements



Method	Time	Temperature	Phenol	Naphthalene
GC-MS	30 min	15°C	215 ppm	16 ppm
Extraction	3 min	150°C	360 ppm	31 ppm
In-situ	3 min	306°C	7700 ppm	1000 ppm


## Conclusions | **Now**

### **In general**

- You can find a lot inspirations for the work on the Earth
- Different research areas can have the same origin
- Scientists can make industry guys happy


### **In particular:**

- Excellent experimental tools are available for (VUV) UV-FIR optical measurements
- Temperature range can be also negative (e.g. gases at low T)
- New data/lines for NH<sub>3</sub>/SO<sub>2</sub>/SO<sub>3</sub>
- New data for phenol/naphthalene
- Try always In Situ and avoid any Ex Situ (extraction) measurements




Conclusions | Future

- Inspiration comes from industry (small, middle large, ...)
- Possible spin offs: innovation (patents)
- New **gas components: CH<sub>3</sub>Cl, KCl etc. (together with UCL)**
- Combine several methods to obtain **multi-parameters**
- ... ?
- Contact: Alexander Fateev  
[alfa@kt.dtu.dk](mailto:alfa@kt.dtu.dk)  
+45 23652906



- To Energinet.dk: projects No. 2013-12027, 2011-1-10622, 2010-1-10422
- To MST.dk
- To DONG Energy and Vattenfall
- To UCL (Prof. Jonathan Tennyson's group)



# Thank you for your attention

